




case
source



Scientific & Laboratory *Equipments*

YOUR ONE STOP SUPPLIER FOR
ALL YOUR LAB NEEDS



Care Source Trading is in the business line of providing a wide array of Scientific & Laboratory Equipment, Medical, Surgical Equipment & Instruments, Medical Rehabilitation & Hospital Equipment, Pharmaceutical, Oil & Gas, Water Testing Products, Food & Beverage, Environmental Education from top manufacturing brands worldwide.

Over the years, our world has been accumulated by the COVID-19 which pushes us to pursue our goal to build a standard of high quality products at very reasonable prices.

We at "Caresource" ensure that we hold ourselves accountable to the highest standards by meeting our customers' needs precisely and completely whenever they patronize our products.

We are continuously evolving to become an industry leader in the vibrant field of Medical Technologies and Life Sciences.

"Caresource" a globally recognized trading company established world-wide with an excellence in products and services. We strive to meet the increasing and diversified demands of clients by providing standard and state of the art products. Having partnered with various world renowned and reputed suppliers across the globe we are able to update our clients of the fast moving trends and have emerged as the most preferred supplier for numerous top end clients in the region.



We as a company are well aware that we have a social impact and commitment as an organization beyond our core business objectives on the world in which we live, and the people we interact with. Our actions impact our employees, our customers, our suppliers, the communities in which we live and work, and the environment. As a responsible and ethical participant in the global community our purchasing policy takes sustainability and ethical sourcing into consideration throughout all stages of the buying cycle.

Table Of Content

Microbiological Safety Cabinets (Sample Preparation)

Biological Safety Cabinet	4
Laminar Flow Cabinets \ Animal Research Workstations	5

Laboratory and Medical Cryogenic Equipment (Sample Storage)

Laboratory Refrigerators	6
Blood Bank Refrigerator \ Combined Refrigerator & Freezer	7
Upright Ultra-low Temperature Freezers \	7
Laboratory Freezers	8

Laboratory Safety Equipment (Chemical Research)

Ductless Fume Hoods	9
Ducted Fume Hoods & Filtered Storage Cabinets	10

Laboratory Equipment

Balance \ Water Bath \ Homogenizer	11
Water Purification System \ Water Distiller	12
Laboratory Stirring and Heating	13
Laboratory Shaking and Mixing	14
Laboratory Oven	15
Laboratory Incubator	16
Laboratory Centrifuge	17
Autoclave	17

Molecular Biology Instruments \ Pathology Lab Solution

PCR Thermal Cyclers \ Real-time PCR system	18
PCR Cabinets Electrophoresis System \ Pathology	18

Pharmacy Compounding \ Other Laboratory Equipment

Compounding Device \ Freeze Dryer \ Dental Oil Compressor	19
Laboratory Test Sieves \ Testing Equipment	19
Moisture Analyzer Chemical & Filtered Storage Cabinets	19

Laboratory Consumables

Laboratory Glassware	20
Plastic Labware \ Laboratory disposable	21
Liquid Handling \ General Labware Supplies	22

Medical Rehabilitation and Hospital Equipment

Hospital Bed \ Medical Trolley \ Medical Chair / Table	23
Rehabilitation Series \ Oxygen Equipment \ Stretcher	23
nPAP \ BPAP \ CPAP	23

Other Equipment

Electric Linear Actuators \ Lifting Columns	24
---------------------------------------------------	----

Temperature and Humidity Data Loggers

Single-use USB PDF Data Logger \ Multi-Use USB Data Logger \ Wireless temperature data loggers \ Food testing equipment	25
-------------------------------------------------------------------------------------------------------------------------------	----

Water Testing Instrument and Testing Strips

Pool and SPA \ Industrial Water, Boiling & Cooling	26
Food , Beverage, Laundry & Sanitation \ Aquarium and Fish Farming \ Water and Wastewater \ Soil	27
Drinking Water \ Environmental Science Education \ Cosmetics \ Homebrew	28
pH Paper \ Qualitative pH Tests \ Non-Bleed pH Strips	29
Reagent Solution \ Healthcare \ Marine Testing kit	29

Microbiological Safety Cabinets (Sample Preparation)

Biological Safety Cabinet



Class II B2 BSC

Standard Accessory

LED lamp*2, UV lamp*1, base stand, remote control, foot switch, exhaust blower, exhaust duct, drain valve, water proof sockets*2, pipe strap*2



BMB-II-'' Laminar-S-'' Class II

The cabinet is used to equip individual work places in medical, pharmaceutical and other institutions working with pathogenic biological agents and microorganisms.



Streamline® Class II BSC

The SC2-E series features a multi-piece & autoclavable work tray for a hassle-free cleaning process.

This model also has glass side walls that provide a brighter work zone.

- Available width sizes: 4 ft and 6 ft



Class II Type A2 BSC NSF 49-certified

Equipped with energy-efficient DC ECM Motor, Sentinel™ Gold Microprocessor Controller, Dynamic Chamber™, ISO Class 3 work zone to ensure overall protection from pathogenic samples.



Labculture® G4 Class II Type B2

with 100% exhaust airflow mechanism provides a high level of containment and user and product protection. LB2 G4 also has fail-safe system where in case of exhaust failure, the cabinet's main fan automatically shuts down to ensure safety.



Labculture® G4 Class II Type A2 BSC

with Centurion Touchscreen controller is NSF-certified and available in three sash height openings: 8", 10", and 12" inches, with standby height that easily activates standby mode.



BMB-III- Laminar -CLASS III

The model design allows using those cabinets for work with deadly bacteria & viruses. Reduction of risk of infection of operator work with airborne pathogenic agents and microorganisms, protection of the environ. as well as the product from external contamination & cross-contamination.



Airstream® Class III BSC

Esco offers a range of Class III Cabinets that provide the highest level of personnel, product and environment protection against agents assigned to biosafety levels 1, 2, 3, and 4.

Microbiological Safety Cabinets (Sample Preparation)

Laminar Flow Cabinets

Vertical Laminar Flow



Cabinet provides sample protection as purified air travels across the working zone of the cabinet in a vertical.

Horizontal Laminar Flow Cabinet



provides a sterile work zone through a purified air that travels in a horizontal, unidirectional stream and leaves the main work chamber across the entire open front of the cabinet.

Clean Bench & Laminar Flow (Horizontal)



Efficient damp-proof and fireproof glass fibre HEPA filter, typical efficiency of $\geq 99.99\%$ for $\geq 0.3\mu\text{m}$ particulate.

Mini Laminar Flow Cabinet, Vertical Type



- Stainless steel worktop
- Ergonomic Control Panel Location
- Centered and angled down for an easy reach & viewing

Animal Research Workstations

Bedding disposal animal workstations



- ELISA-verified containment
- ULPA Filter and carbon filter to absorb odor
- Motorized height stand
- Integrated waste bin
- Available size: 4ft

Dual access animal workstations



- Lowest energy
- Lowest noise at ≤ 53 dBA
- Legroom in both sides
- ELISA tested
- Available size: 4ft and 5ft

Universal animal workstations



- ELISA-verified containment
- ULPA Filter and carbon filter to adsorb odor
- Biosafety cabinet class II containment
- ISO Class 3 work zone
- Available size: 4ft and 6ft

Innovive Mouse Animal Transfer Station



- Optimized for innovove mouse cages
- Divided work surface for workflow
- Powerful push-pull airflow design

Laboratory and Medical Cryogenic Equipment

Laboratory Refrigerators



Pharmacy / Medical Refrigerator Lab

- Temperature range in 2°C ~8°C. And it comes with 1" high-brightness digital temperature display ensuring the display precision in 0.1°C.



Lab Refrigerator Touchscreen Controller

- Temperature ranges from +2°C to +15°C.
- Available sizes: 347L, 620L, and 1355L



Laboratory Refrigerator

- Made of high-quality cold-rolled steel plate, environment-friendly ceramic and spraying surface.
- Temp. Range: 2°C~8°C



HP Series Lab Refrigerator

Standard Controller

- Temp. Range: +2°C to +15°C
- Available sizes: 128L, 347L, 620L, and 1355L



YC-315EL pharmaceutical grade

Equipped with multi-duct vortex refrigeration system and finned evaporator, which can prevent the frost completely and improve the temperature uniformity to a large extent.



Spark Free Refrigerator

- ATEX II C-T6 E.U. Explosion Proof Certification
- 3~16°C Setting Temp. range
- One-touch Search for Historic Data
- High Efficiency HC Cooling Technology

Undercounter medical refrigerator



Comes w/double layer tempered glass door, having the features of anti-condensation and electrical heating. Temperature range 2~8°C Ambient temp. 16-32°C



Undercounter Vaccine Refrigerator

Equipped with intelligent temperature controller and brings out constant temperature. Adopt double layer foamed solid door, high efficiency heat preservation

Laboratory and Medical Cryogenic Equipment

Blood Bank Refrigerator



Blood Bank Refrigerator

- Temp. Range: $4 \pm 2^{\circ}\text{C}$
- Blood Bags (450ml)
10*36=360 pcs
- Capacity: 626L
- Blood Bags (450ml)
16*36=576 pcs
- Capacity: 966L

Refrigerator & Freezer



Vaccine Refrigerator Medical For Vaccines

- Refrigerator: $2^{\circ}\text{C} \sim 8^{\circ}\text{C}$;
- Freezer: $-10^{\circ}\text{C} \sim -25^{\circ}\text{C}$
- Capacity:
- Refrigerator: 198L
- Freezer: 102L



Blood Bank Refrigerator

- Temp. Range: $4 \pm 2^{\circ}\text{C}$
- Capacity: 86L Blood Bags (450ml) • 136L Blood bags: 99pcs (450ml)
- 296L Blood Bags 156pcs (450ml) • 356L Blood Bags: 195pcs (450ml)



Combination & Freezer Standard Controller

- Temp. Ranges from $+2^{\circ}\text{C}$ to $+15^{\circ}\text{C}$ for the
- Refrigerator and -10°C to -24°C for the freezer.
- Capacity: Freezer: 160 L (5.7 cu. ft., Refrigerator 260 L (9.19 cu. ft) Freezer 265 L (9.77 cu. ft)



Blood Bank Refrigerator

- Cooling Performance 4°C
- Temperature Range $2^{\circ}\text{C} \sim 6^{\circ}\text{C}$
- Equipped with 6 stainless steel drawers;
- Can hold 312 blood bags in 450ml for each.



Combined Refrigerator And Freezer

- Upper temperature in a range of $2^{\circ}\text{C} \sim 8^{\circ}\text{C}$ and lower temperature in a range of $-10^{\circ}\text{C} \sim -40^{\circ}\text{C}$
- Standard with Build-in USB datalogger

$+4^{\circ}\text{C}$ $+22^{\circ}\text{C}$ Blood Transport Box

- Dual temperature regulation, LCD display
- High precision temperature sensors
- International well-known brand compressor
- High-efficiency condensation fan



Combination refrigerator freezer

- High-efficiency
- Refrigerating system
- High-precision
- Computerized temperature control system
- Comprehensive security system
- With upper $2^{\circ}\text{C} \sim -8^{\circ}\text{C}$ and lower $-10^{\circ}\text{C} \sim -26^{\circ}\text{C}$



Laboratory and Medical Cryogenic Equipment

Upright Ultra-low Freezers



Low Temperature Freezer Vertical Type

- Temp. range: $-15^{\circ}\text{C} \sim -45^{\circ}\text{C}$, adjustable
- Refrigerant: Mixed-gas (CFC Free)
- Capacity: 408L
- Defrost: Manual

Freezers



Medical Deep Freezer Lab Freezer

- Capacity: 268L / 528L
- Type: Vertical
- Temp. Range: $-30^{\circ}\text{C} \sim 40^{\circ}\text{C}$ / $-20^{\circ}\text{C} \sim -40^{\circ}\text{C}$

Ultra-low Temperature Medical Cryogenic



- Refrigerator Vaccine Freezer
- Capacity: 588L / 728L / 838L
- Type: Vertical
- Temp. Range: $-40^{\circ}\text{C} \sim -86^{\circ}\text{C}$

HP Series Laboratory Freezer



Standard Controller

- Temp. Range: HF2 model -10°C to -25°C and HF3 model -25°C to -40°C .
- Available sizes: 128 L, 347L, 620 L, and 1355 L

Ultra-Low Temperature (ULT) Freezers



- Temp. Range: -50°C to -86°C are widely used in scientific research for longterm storage of samples.
- Available sizes: 363 L, 480 L, 597 L, and 714 L



CE FDA

Chest Freezer

- Capacity (Lcuft): 105/3.70, 485/17.12
- Temp. Range ($^{\circ}\text{C}$): $-60 \sim -25^{\circ}\text{C}$
- Advanced Cooling System: High performance compressor, reasonable refrigeration layout, more stable refrigerant

Cryogenic Freezer Ultra Deep Freezer



- Unique, high-efficient and recycling cooling system
- Superior leader in extremely low temperature
- VIP vacuum 3 dimensional thermal insulation
- Single-pole lubrication compressor refrigeration technology



Ultra-Low Temperature (ULT) Freezers

- Temp. Range: -50°C to -86°C are widely used in scientific research for longterm storage of samples.
- Available sizes: 363 L, 480L, 597 L, and 714 L

Laboratory Safety Equipment (Chemical Research)

Ductless Fume Hoods



School Laboratory Ductless Fume Hood

Standard Accessories:

- Fluorescent Lamp, Base cabinet, Total load of 2 waterproof sockets: 500W; Chemical Filter.

External Size (W*D*H):

- 1000*830*2140mm
- 1200*830*2140mm
- 1500*940*2140mm
- 1800*940*2140mm



Powdermax™

- Ideal for handling powdered chemicals
- Equipped with HEPA filter
- Phenolic worktop for lesser vibrations.
- Available Sizes: 3 and 4 ft.

Ascent™ Opti Titramax Specifications:



Offers excellent containment and ergonomic features at a great value. This compact-sized and simplified ductless fume hood is complete with internal lighting, worktop, and microprocessor control system



- Ideal for titration applications
- Equipped with carbon filter
- Has taller workzone and a horizontal sliding sash
- Available Sizes: 3 and 4 ft.

Ascent™ Max – B Series

- Standard model
- Has a main carbon filter
- Optional VOC Sensor
- May have provisions for PP drip cup, swan neck faucet and service fixtures.
- Available Sizes: 2,3,4,5,6 ft.



Ascent™ Max – E Series

provides operator and environment protection by filtering out chemical fumes and recycling clean air directly back to the laboratory. Unlike conventional fume hoods, these hoods provide energy savings, mobility and convenience as you do not have to deal w/complicated ducting systems.


Mini Ductless Fume Hood, Vertical Type, FMH-550N

- HEPA filter (ISO Class 5 work-zone)
- Antimicrobial powder coating
- Standby mode for more energy savings
- Stable and self-compensating airflow



Ductless Fume Hood, FMH Series

- 99.995% high efficiency filtering
- Advanced VOC Detector port
- LED touch screen control system
- Silent turbine fan
- Explosion proof lighting system
- Transparent acrylic glass >6mm thickness



Laboratory Safety Equipment (Chemical Research)

Ducted Fume Hoods



Frontier® Mono

Is generally applicable for common laboratory applications such as boiling, evaporation, drying, and other applications that emit noxious fumes and vapors.

- ASHRAE 110-2016 certified
- Single wall design
- Worktop and service fixtures are installed on the base cabinet



Frontier® Acid Digestion

- ASHRAE 110-2016 compliant
- Tri-wall construction
- Designed for acid-digestion applications (except perchloric acid)
- Built with u-PVC or PP internal surface has polycarbonate sash to prevent etching.
- Available sizes: 4, 5, 6,8 ft



Frontier® Acela Mining

Designed specifically for users in the mining industry. It has a 100mm deeper workzone to help contain chemical splashes and spills from highly corrosive chemicals.



Frontier® Acela XP

- ASHRAE 110-2016 certified
- Tri-wall construction
- Low energy-consumption, high performance fume hood
- 5° sloped front sash design
- Superior containment at 0.3 m/s face velocity
- Available sizes: 4, 5, 6,8 ft

Chemical & Filtered Storage Cabinets



Ascent™ Storage Cabinet –A Series

- Standard model
- Has a main carbon filter
- VOC Sensor
- PP Trays
- Available in 2,4,6 ft.



Filtered Storage Cabinet, CSC-F800, F820, F1600

- Remote monitoring system
- Anti-corrosive and anti-rust performance
- 99.99% high efficiency filtering
- Advanced VOC Detector port detects pollution. in time, with special alarm system



Sure-Grip® EX Classic Safety Cabinets 89-CL Justrite flammable cabinet White

Designed specifically for users in the mining industry. It has a 100mm deeper workzone to help contain chemical splashes and spills from highly corrosive chemicals.



Chemical Storage Cabinet (Undercounter), SSC-4Y,4R,4B

- Color: Yellow, Red, Blue
- Insulation for fire resistance
- 50MM leak-proof liquid tank
- External Dimension (W*D*Hmm): 560x430x430

Laboratory Equipment

Balance



Analytical balances
Max. Capacity: 100g; 110g;
120g; 200g; 210g; 220g;



Electronic analytical balances
Readability Range:
0.1mg – 0.01mg.



Halogen Moisture Analyzer
Readability: 0.001g; 0.002g;
0.005g; 0.01g



Moisture Balance
Range 0-220g Accuracy 0.005g
Moisture readability 0.01%



Micro Analytical Balance
Readability: 0.01mg/0.1mg



Semi-Micro Analytical Balance
Readability: 0.00001g/0.0001g

Water bath



CYCLE WATER BATH
suitable for thermostatic, baking,
dewaxing, sterilization



Thermostatic Shaking Water Bath
Temp. Range: RT~100°C



Tissue Flotation Water Bath
Temp. Range: RT to 90°C

Ultrasonic Water Bath



Ultrasonic bath thermostatic
oscillator Temp. control
Range 0-99.9°C



Ultrasonic water bath
Available Size: 2L, 3L, 6L, 10L
Heating Temp. 20-80°C



Ultrasonic Cleaner Single
Frequency Type

Water Purification



Small Screen
Utrapure Water Purifier
2 water outlets RO & UP water



Type I and Type III RO Water
Purification System MTONT-1D



Deionized Water Purifier
RO Pure water: desalination rate
as high as 95-99%, TDS<10ppm

S.Steel Water Distiller



Automated shut-off water distiller
MAWD-1C



Standard electric
water distiller MEWD-1A
Water output capacity 5 L / hr



Tower steam water distiller
MTSD-1C Water output
capacity ≥ 200 L / hr

Thermal Control



LED Digital
Double Modules Dry Bath range
of temp. control up to 105°C



MiniHCL 100 Mini Dry Bath
Temperature range: 0-100°C



HCM100-Pro Thermo Mix
(Mechanical fixation)

Homogenizer



Homogenizer
No. of Samples (Capacity) 1~24
samples (24 x 2 ml, 12 x 7 ml)



Ideal homogenizer
Capacity 3 X 2 ml
Speed Range 2800 to 4000 RPM



Handheld Homogenizer
Processing volumes
from 0.1-50mL or 1-250mL

Laboratory Equipment (Stirring & Heating)

Hotplate Stirrer	Hotplate	Magnetic Stirrers	Overhead Stirrer
			
Pro LCD Digital Magnetic Hotplate Stirrer With 10" Ceramic Plate Speed Range: 100 -1500rpm Max. heating plate temp. 500°C	Hot plate Stainless steel electrothermal plate Platform Dim. (mm) 200x150mm Heating power 500W	MS6-Pro LCD Digital Magnetic Stirrer Speed range: 200-1500rpm Work plate Dimension: 140x140mm	OS20-Pro LCD Digital Overhead Stirrer Speed range: 50-2200rpm Max. stirring quantity[H2O]: 20L
			
LCD 4-Channel Digital Magnetic Hotplate Stirrer Speed range: 200-1500rpm Work plate Dim: Ø 135mm(5") x 4	Intelligent temperature hot plate Temp. range RT~300°C Platform Dim. (mm) 200x150mm	MS-PA LED Digital Magnetic Stirrer Speed range: 200-1500rpm Work plate Dim: Ø 135mm(5 inch)	OS70-Pro LCD Digital Overhead Stirrer Speed range: 50-1100rpm Max. stirring quantity[H2O]:70L
			
MS7-H550-S LED Magnetic Hotplate Stirrer With 7" Ceramic Plate Platform Dim.(mm) 200x150mm	i Stir Large Capacity Stirrers Max. Capacity 200 litres Variable Speed 100 – 600 RPM	Ceramic magnetic stirrer Speed range start up ~1600 rpm Temperature range 50~320°C	iStir OH Prime Overhead Stirrer Max Speed: 2000 RPM Max Capacity: 40 L
			
10-Position Magnetic Hotplate Stirrer Max speed 1100rpm,Max.temp 120°C Work plate Dim: 180x450mm	HP380-Pro LCD Digital Hotplate Work plate Dim: 140x140mm Overheating temp. protection: 420°C	iStir MS10 Magnetic Stirrer Max Speed: 200 to 2200 RPM Max Capacity: 10 L	iStir OH Elite Overhead Stirrer Max Speed: 2000 RPM Max Capacity: 100 L
			
LCD Digital Magnetic Hotplate Stirrer w/Timer Dig. temp.control up to 340°C Dig. speed control up to 1500rpm	HP500-Pro LCD Digital Hotplate Work plate Dimension: 254x254mm Overheating temp. protection: 540°C	iStir Uno Magnetic Stirrer Max Speed: 1500 RPM Max Capacity: 800 ml	iStir OH Jr. Overhead Stirrer Max Speed: 2200 RPM Max Capacity: 10 L

Laboratory Equipment (Shaking & Mixing)

Vortex Mixers



MX-C Cell Disruptor
Orbital diameter: 4mm
Speed range: 0-3000rpm
(Adjustable)



MX-S Variable speed Vortex Mixer
Variable speed of 0 to 3,000rpm
for gentle shaking to rapid
mixing of samples



**Multi-Tube Vortex Mixer
(MS-2500)** Table size (mm)
310x180 Speed
range 500-2500rpm/min



Mini Vortex Mixer VORTEX-2
Shaking Orbit 4.5mm
Loading Cap.(one tube) Max.
50ml/tube



Mini Vortex Mixer VORTEX-1
Mixing Method Circle
Shaking Rotational
Speed 4000rpm

Microplate Mixers



Microplate Mixer Motion type:
Orbital Speed range Single
microplate: 0-1500rpm|Double
microplate: 0-1000rpm



Microplate Oscillator ZJ-201A
Clamp type: hemagglutination
plate Speed range:
Start up-2600rpm



Digital Microplate Shaker
Max Speed: 1200 RPM
Max Capacity: 4 Microplate



iShak BL Uno VT
Max Speed: 1800 RPM
Max Capacity: Single micro-plate



Microplates Shaker BK-TS100
Sample Capacity: 4plates
Speed Range: 200~1500rpm


Rotators/Rocking



**MX-RD-E Effective affordable
mixing** Speed controlled by Scale
Adjustable speed range
from 0 to 80 rpm



MX-T6-Pro LCD Digital Tube Roler
Speed range: 10-70rpm
Motion type: Rocking and rolling



**LCD Digital Tube
Rotator, Horizontal**
Tilt angle: 0-90° \ Rotation
angle: 360°



**MX-RD-Pro LCD Digital Tube
Rotator** Motor type: Brushless DC
motor Wide variety of accessories
are available



Blood mixer ZM-7D
Motion type :Roll & swing
Speed range: 20-80rpm

Shakers



**SK-R330-Pro LCD Digital
Rocking Shaker**
Rocking motion angle 9°
10kg and speed range 10-70rpm



**SK-D3309-Pro LCD Digital 3D
Shaker** Max. load capacity of 5kg
with platform
Speed range of 10-70 rpm



**LCD Digital Orbital
Shaker 7.5 kg w/platform &
speed range 100-500 rpm**
Maint. free brushless DC motor



iShak 3D-5 NXT Shaker
Max Load: 5 to 7 kg
Max Speed: 120 RPM



Shaker RTS-200B
Max Capacity: Δ100ml×16 or
Δ250ml×12 or Δ500 ml×9
or Δ1000ml×4

Laboratory Equipment

Drying Oven

Muffle Furnace



Lab Vacuum Drying Oven
Size: 23L, 53L, 91L, 213L, 91L,
213L Temp. Range: 50~200°C



**Dual-use Drying Oven
Incubator Sterilizer**
Incubator: RT+5°C~80°C;
Oven: 80°C~220°C



**Benchtop High Temperature Hot
Air Circulation Drying Oven**
Temp. Range: RT+20~400°C



Muffle Furnace MX Series
Max.Temp.(c) 1000 / 1200
Capacity(L) 6 8 16 30 6 8 30



**Vacuum Dry Oven
(DZF-6090/DZF-6210)**
Volume 90L 210L
Temperature range 50~250°C



**Infrared Fast Heating Drying
Oven, DON-IF Series**
Volume(L): 43, 81, 138, 252
Temp. Range: RT +10~250°C



Big Forced Air Drying Oven
Vol: 640L, 1000L, 1300L, 1870L,
3070L Temp. Range:
RT+10-250°C, RT+10~300°C



Muffle Furnace
Max. Temp.: 1200°C
Continuous working temp.:
≤1100°C



Laboratory Drying Oven
Temp.Range Ambient +5 °C to
300 °C
Capacity: 53 litres




Forced Air Drying Oven
Capacity: 45L, 54L, 75L, 88L
Temp. Range: RT+10°C~300°C



**Constant Temperature
Drying Oven** Capacity: 43L, 55L,
72L, 138L, 270L Temp. Range:
RT+10°C-250°C



**Laboratory chamber
furnace, vertical lift door**
Temp. 1.000°C – 1.200°C
-1.300°C – 1400°C



CE FDA

Dry Oven
Volume: 25L 50L 70L 105L
Temperature range RT+10-200°C



Forced Convection Lab Oven
Pre-heat Chamber Technology
4-zone heated air jacket



CE

High-temperature-oven
High Temperature Oven,
DON-H130, H220, H640



CE

**Muffle Furnace, Box-type,
FNC-BX-R Series**

Laboratory Equipment

CO2 Incubator



CelMate® CO₂ Incubator
Direct heat and air jacket
Volume: 50 L, 170 L, and
240 L

Shaking Incubator



**Large Capacity Vertical
Type Shaking Incubator**
Double Door Double Layer
Mode: (BJPX-X)

Biochemical incubator



**Intelligent biochemical
incubator**
SPX-50B/80B/150B/250B

Incubator



**Isotherm® Natural
Convection Lab Incubator**
Model: INA



**Isotherm® Refrigerated
Incubator** Electrogalvanized
steel body construction



CelCulture® CO₂ Incubator
CO₂ & O₂ Control, Copper
Chamber, UV Lamp



**Tabletop Constant
Temp. Shaking Incubator**
Control Temp. Range:
RT+5~60°C



CE FDA ENEC

**Cooling Biochemical
Incubator**, Interior Vol:
175,275,375,475,800,
1075L T. Range: -10~75 °C



**Isotherm® Forced
Convection Lab Incubator**
Model: IFA



**Isotherm® Refrigerated
Incubator** Stainless steel
external construction



CelCulture® CO₂ Incubator
CO₂ Control, UV Lamp,
Stainless Steel Exterior



Shaking incubator
capacity 140L 280L
Temp. Range 4~60°C 4~60°C



Lab Biochemistry Incubator
Capacity:
100,150,200,250L
Temp. Range: 0~60 °C



**Medicine Stability Test
Chamber** Capacity: 173L,
288L, 504L
Temp. Range: -20~+65°C



**Electrothermal Constant
Temperature Incubator**
Model: BJPX-H



Infrared CO₂ Incubator
Capacity 80L 160L
Temp. range Room
temp. +5~50°C



Shaking incubator
RF-211B/CF-111 Temp.
range 4°C~60°C
RT+5°C~60°C



Biochemistry Incubator
Cap. (L) 80 100 150 200
250 300 400 Temp. Control
Range 0~65°C



iTherm CH25
Max Temp: Ambient
-15°C to 60°C
Max Capacity: 25 L



Anaerobic incubator
Temp. range: Room
temp.+5~50°C Chamber
size: 250x190x290

Laboratory (Disinfection & Sterilization)

Autoclave (MEDICAL)

Autoclave (DENTAL)

Autoclave (LABORATORY)

Gas Sterilizer

Labware Cleaning Device



**SA-260MB Class B
Autoclaves Chamber**
Vol: 24 L Chamber Size Ø
260 x 450 mm



**SA-300MB Class B
Autoclaves Chamber**
Vol.40L Chamber Size Ø
300 x 570 mm



**Prime 30L advanced
full-color touch
panel & chamber 316L
SS.Volume: 30 L**



CE

**Hydrogen
Peroxide Plasma Sterilizer**
Chamber Vol:108,135,192L
Working temp.:40-60°C



CE FDA

**Automatic Glassware
Washer & Dryer**
Size:120L area: 90/120/20
0/220/320/420SS



**SA-230FA Fully automatic
autoclave,
Chamber Volume: 16L**



**SA-260FA Reliable &
economical automatic
autoclave Volume: 24 L**



**SA-300VLA Fully
automatic vertical autoclave
Chamber Volume: 50 L**



CE

**Portable Pressure Steam
Sterilizer Electric or LPG
heating type, Vol:18L, 24L**



CE FDA

**Automatic Glassware
Washer and Dryer
Capacity: 320L**



**SA-300H semi-automatic
autoclave Vol.40L Chamber
Size Ø 300x570 mm**



**Table Top Class B
Autoclave Size:18L 23L
Working Temp. 121/134°C**



**SA-300VF Reliable &
economical automatic
autoclave Chamber 50 L**



**Hot air sterilizer HAS
Series Capacity: 48L 80L
105L 180L**



**UC-400 Simple,
Practical Ultrasonic Cleaner
Inner Tank Capacity 22 L**

Autoclave (BEAUTY AND VETIRENARY)



**SA-232N Class N
sterilization of unwrapped
materials Chamber Vol:16L**



**Prime 17B Class B Tabletop
Autoclave Chamber Vol.17L
Chamber Ø 240 x 360 mm**



**SA-232X Microprocessor
controlled semi-automatic
sterilizer Chamber Vol:16 L**



**SA-230 Autoclaves with
Traditional Mechanical
designs Chamber Vol:16 L**



**SA-232V Most
economical & practical
autoclave Chamber Vol:16**

Laboratory Equipment

Palm Mirco Centrifuges



Mini-Centrifuge LX-120T2Z
Max speed (r/min): 12000
Max Capacity: 8x1.5/2.0 ml
Max RCF(xg): 7325

High Speed Centrifuges



Tabletop Refrigerated Centrifuge TCR-1500-8
Max RCF: 21382 x g
Max Speed 15000 rpm
Max Vol: 6 x 250 ml

Low Speed Centrifuges



Low-speed Centrifuge
Max. RCF: 2600xg, increment: 10g
Speed Range: 300-5000rpm
Rotor: 1.5-5/7/10/15mL/x6


Other Specific Function Centrifuge



DM1424 Hematocrit Centrifuge
Speed range: 200-12000rpm
Max. RCF: 13680xg Rotor size: 24x capillary tubes



D1008 Palm Micro Centrifuge
Max. Speed: 7000rpm
Max. RCF: 2680xg



Benchtop High-speed Refrigerated Centrifuge LX-165T2R
Max Speed (r/min): 16,500
Max RCF (xg): 25,872



Low Speed Refrigerated Centrifuge
Max speed: 6000RPM
Max RCF: 6880xg
Max capacity 6x1000ml



Cytology Centrifuge
Max. Speed: 4000rpm
Max. RCF: 2170xg
Max. Capacity: 6 cards



New Mini centrifuge LC-05MC
Max RCF 2500 x g
Speed 300~5000 r/min



High speed centrifuge Model HC-20C
MAX RPM 20000
RPM Max RCF 26500xg



Versati™ Micro Ventilated Centrifuge
Max RCF: 21382 x g
Max Speed 15000 rpm
Max Vol: 44 x 1.5 / 2.0 ml



Hematocrit centrifuge Model HC-12C plus
MAX RPM 13000 RPM
Max RCF 17200xg



Mini centrifuge MC-04/07/MC-12
MAX RPM 4000/7000/12000 RPM



High-Speed Refrigerated Microcentrifuge
Max. Speed 15800rpm
Max. RCF 23444xg
Max. Cap. 5mLx10



DM0424 Multi-Purpose low Speed Centrifuge
Max. RCF: 2500xg
Speed Range: 500-4000rpm




Hematocrit Centrifuge HC-12A
Max RPM 12000 RPM
Max RCF 15300xg Rotor: 1.5x75mmx 24 capillary tubes

Molecular Biology Instruments \ Pathology Lab Solution

PCR Thermal Cyclers	Real-time PCR system	PCR Cabinets	Electrophoresis System	Pathology
---------------------	----------------------	--------------	------------------------	-----------



CE



MiniPro® Thermal Cycler
low cost personal T. cycler
compact footprint.

Real-time PCR system,
PCR-Q96 Series
Fluorescent channels:5/6

Streamline® Polymerase
Chain Reaction Cabinet
Size:2ft Provide ISO Class3

Western Blot
Electrophoresis Tank
BK-TET01

Laminar Flow Pathology
Workstation



Aeris™ PCR Thermal Cycler
consumable PCR tubes,
strips, plates and slides,

Fluorescence Quantitive
Pcr Detection System
Thermal

Airstream® Polymerase
Chain Reaction Cabinet
equipped with HEPA
filtered laminar flow

Vertical Electrophoresis
Tank BK-VET02 NO. of
Samples: 10~40pcs
Buffer Vol: 1000ml

Minux® FS800A Cryostats
With a fully automated,
user-friendly operating
system



ProGene Real-Time PCR
Thermal Cycler

Extract Automated Nucleic
Acid Extraction System
Sample S.:32vol:20-1000µl

PCR Cabinet Pre-Filter:
Polyester fiber,W.HEPA
Filter:99.995% at 0.3µm.

Electrophoresis Apparatus
Power sup.GEP-PH-600D
Testing temp:-20℃~+85℃

Minux® S700
Semi-Automatic Rotary
Microtome

Cell and Molecular Biology



M2-96G Gradient Thermal
Cycler Heating block
96-well

C100-Pro Automated
Cell Counter

C100/C100-SE Automated
Cell Counter identify both
live and dead cells.

DSC-800 Single Cell
Suspension Dissociator
Sample volume:20-4000mg

DSC-400 Single Cell
Suspension Dissociator

Pharmacy Compounding \ Other Laboratory Equipment

Compounding Device



Gako Wetmill
3-in-1 concept: compound, store, and dispense

Freeze Dryer



Vacuum Lyophilizer Freeze Dryer
•Cold Trap Temp. $\leq -60^{\circ}\text{C}/-80^{\circ}\text{C}$
•Cold Trap Cap: 9.3L

Dental Oil Compressor



Medicair Line oil-free Compressors can supply compressed air from 1 to 8 dental chairs.

Lab. Test Sieves



Stainless Steel Test Sieve NL 1010 X Standard: BS 410 / I.S.O.3310 parts 1 & 2, ASTM E11:87

Soil Tester Moisture Analyzer



Soil Tester Nutrient Content Soil Nutrient Tester



Gako UV-C Air Sterilizer
Disinfects 800m³ of air w/ in 60 Min. 99.9% disinfection efficiency



Vertical Freeze Dryer
•Cold Trap Temp. $\leq -56^{\circ}\text{C}/-80^{\circ}\text{C}$ (Optional)
•Cold Trap Capacity: 23L



SIL-Dry Line OF range dental compressors (available with and without dryer)



Test Sieve NL 1010 X Standard: BS 410:1986 Available in 200 & 300 mm diameter



Sension+ Benchtop Meters
Parameters: pH, mV, ISE, ORP/Redox, Cond. TDS, Salinity, Resistivity, Temp.



Gako InvoMatic
Advanced 3-axis mixing technology for compounding



Pilot Freeze Dryer PF02
LCD touch screen, PID intelligent control system, program. freeze-drying



Air Lab Range Oil-free compressors ideal for dental technicians & laboratories.



Multi Amplitude Triple Motion Sieve Shaker Standard: EN932-5, AASHTO T 27 T. 1-60min.



Moisture analyzer WBA-110M 0,01-110g Ideal for: measuring the percentage of moisture content



Unguator 2100
Employs four on-board microprocessors
•Fully automatic



NovaDryer-LF400
4-6Kg/9-13lb -60°C Low Temp. Freezer Dryer for Lab, Pharma & Home Use



Oil Free Air Compressor
Rotation Speed: 1450rpm
Gas Tank Capacity: 24L 38L 60L



Triple Motion Sieves Shaker NL 1015 X / 010 Standard: EN 932-5, ISO 3310-1



Moisture Analyzer Balance NL 1022 X / 003 Capacity 110 g Weight Resolution 0.005 g

Laboratory Glassware

Beakers / Funnels	Burettes	Glass Flasks	Graduated Cylinders	Bottle	Test Tube
					
Beaker Low Form w/Spout	Burette Amber Class A With PTFE Stopcock	Volumetric Flask Class A	Measuring Cylinder ASTM E1272 Class A	Amber Reagent Glass Bottle Screw Cap	Boros Test Tube w/ Screw Cap
					
Heavy Duty Beaker	Automatic Zero Burette Class A	Volumetric Flask Class B ASTM	Safety Measuring Cylinder	Clear Reagent Glass Bottle Screw Cap	Test Tubes Borosilicate glass 3.3
					
Beaker Tall Form ASTM-E960	Schellbach Burette Class A	Boiling Flask with 2 Necks - Round Bottom	Measuring Cylinder Class B - Squat Form	Heavy Duty Barnes Dropping Screw Cap	Test Tube plain with Bakelite Screw Cap
					
Watch Glasses 3.5" Cover Lids	Automatic Zero Burette Class B	Florence Boiling Flask Round Bottom N. Neck	Measuring Cylinder Class B Round Base	Reagent Bottle Narrow Mouth	Test Tube Stand PP autoclavable
					
Separating Funnel Pear Shaped P.Stopper	Burette, Automatic Self-Zeroing Class A	Erlenmeyer Flasks N.Neck Conical Shape	Meas.Cylinder Class-B Detachable, Hexa.Base	Aspirator Bottle with Screw Cap & Outlet	Blue Plastic Test Tube 50 Peg Drying Rack
					
Filter Funnel plain 60 angle	Stopcock - 3 way PP leakproof stop	Filtering Flask Boro 3.3 - Conical Shape	Graduated Cylinders Detachable HexBase	Glass Reagent Bottle with Acid Proof PP	Lab Starter Kit

Laboratory Disposables

Plastic Labware

Lab Supplies

Laboratory Safety Supplies



BEAKER PP
autoclavable



Measuring Jug PP
Screen Printed



Wood splints
for laboratory setting




Lens Paper low linting
and low shedding



White Color
Microscope GlassCover



Disposable Face Mask



Polypropylene
Cylinders RoundBase



Filter Funnel, P.P
Chemical Resistant



Neoprene Stoppers
1 Hole-ASTM



Magnetic Stir Bar
48 Lx10mm Diameter



Unground Edge Glass
Microscope Slide 7102



Nitrile Examination
Gloves (Powder Free)




Volumetric Flask
PP Autoclavable



Burette, Acrylic ClassB
PTFE Key Stopcock



Glass Fibre Filters
Grade 50C - Medium



Glass Stirring Rods,
7.9" - Rounded Ends



First Aid Kit Portable
for 1-5 persons



Sterile Latex Surgical
Gloves Powder Free



Medicine Measuring
Cup



Scoops w/Knife Edge
7.9" - PP Dual Ended



Ashless Filter Paper
Grade 353 - Medium



Ashless Filter Paper
Grade 352 - Medium



Corrugated Paper
Sharp Container



Gloves Disposable
Vinyl



HPLC Safety Cap
Spec. designed O-ring



Wash Bottle Wide
Mouth Vented Cap



Filter Papers
Grade 304-Medium



Filter Papers Grade
322 - Fast Filtration



Disposable Bed Roll
Non-Woven



Safety Goggles
Direct Vent



Media Bottle
Made of USP Class VI



Reagent Bot.Avail.
PP,HDPE&LDPE,USFDA



Disposable waste bag
autoclavable



Nylon Cleaning Brush
with Fan-Shaped End







































Coverall Disposable
Isolation Suit 40gsm



Safety Glasses Vented
Polycarbonate Lens

Laboratory Consumables (Liquid Handling)

Cell Culture	Liquid Handling	Pipette	Filtration	Molecular Biology	Labware Supplies
					
Cell and Tissue Culture Flasks	Serological Pipets S:1-2-5-10-25-50mL	HiPette Fully Autoclavable	Tube Vacuum Filters System	Pipette Micro Tips	Mortar & Pestle Glazed 125mm
					
Cell and Tissue Culture Dishes	Transfer Pipets Spec: 0.2,1.0, 3.0mL	dPette+Multifunctional Elect.Range:1000µL	Syringe Filters Spec: 13,25,30mm	ZEROTIP® Pipette Micro Tips	Porcelain Mortar & Pestle Heavy Duty
					
Cell and Tissue Culture Plates	Centrifuge Tubes	Electronic Pipette Intelligent sleep mode	Filter Plates	Robotic Tips w/filter & w/out filter	Glass Alcohol Burner Spirit Lamp with Wick
					
Bio-Reaction Tubes	Plastic Centrifuge Tube Racks	StepMate Stepper Vol. Range: 0.50,1.25,2.50 ,5,12.50,20,50.00mL	JetSpin™ Centrifugal Filters Spec.: 0.5mL 5mL 15mL	Micro Centrifuge Tubes	Crucible Tong Straight, Length 20cm, Brass
					
Culture Tubes Size: 4,5,8,14mL	Square Media Bottles	dTrite Electronic Burette	Manifolds Vacuum Filtration	PCR Tubes	Tong Beaker - Silicon covered jaws
					
Cryogenic Vials Type:Flat Socket	DispensMate Bottle Top Disp.	Pipette Controller Autoclavable tip cone	Vacuum Bottle Filters Membrane Type:MCE NYLON PVDF CA SFCA	Lid Lock Micro Centrifuge Tubes	Spatula Spoon 9" Stainless Steel - Flat End & Scoop End

Medical Rehabilitation and Hospital Equipment

Hospital Bed	Medical Trolley	Medical Chair / Table	Rehabilitation Series	Oxygen \ Stretcher	nPAP \ BPAP \ CPAP
					
YFC161L Single Function Manual Bed	YFZ026 ABS Bedside Cabinet	YFHS-W05 Hospital Waiting Chair	YF-E200 Electric Wheelchair	Portable Oxygen Cylinder Kit	G3 BPAP System (G3 LAB) No:G3 LAB
					
YFC261K(VI) Two Function Manual Bed	YFT005 Overbed Table	YFHS-C09 Nurse Chair	YF869LJX Aluminum Wheelchair	Oxygen Cylinder Regulator	RESmart GII BPAP System (Y-30AT)
					
YFD3618K(I) Three Function Electric ABS Emergency Trolley	YFS001-II ABS Emergency Trolley	YFY-R03 Rehabilitation Recliner Chair	YF-CO02 Commode Wheelchair	SO1 5B oxygen concentrator	Auto CPAP System (M1 Mini)
					
YFD5638K(II)5 ICU Bed w/Scale	YFS-C02 Metal Emergency Trolley	YFC-S05 S.S Examination Table	YF-WR01 Rollator	YFTC-J2B(II) Manual Patient Transport	G3 Auto CPAP System (G3 A20) No:G3 A20
					
YFD5638K(V) Bariatric ICU/CCU	YFS-RH01 Patient Record Holder Trolley	YFC-H08 Hydraulic Examination Table	YF-WK05 Walker	YFTC-Y4A(II) Hydraulic Transport Stretcher	G2S Auto CPAP System (G2S A20)
					
YFD8688K 8 Electric ICU/CCU Bed w/scale	YFQ-L08 Cleaning Linen Trolley	YFC-D03 Electric Examination Table	YF-WK04 Walker	YFTE-SB01 Spine Board	Polypro H2 Series

Other Equipment

Electric Linear Actuators



TIMOTION's MA1 series linear actuator is the proven choice for applications requiring a durable, long life solution. Specifically designed for harsh working environments, the MA1 linear actuator is ideal for use in heavy-duty machinery, industrial equipment and off road vehicles. This linear actuator has been certified for applications requiring IP69K compliance.



TIMOTION's MA2 series electric heavy duty linear actuator was specifically designed for applications that face harsh working environments and require heavy-duty and durability. Its IP69K protection ensures it will withstand high-pressure water jets and the ingress of dust and other solid contaminants.



TIMOTION's TA14 linear actuator is designed for lift applications like recliners, lifting chairs and movie theater seating. This linear actuator is designed to function as a direct cut system, eliminating the need for a control box, offering a simple and economical alternative. Options for the TA14 include a safety nut and multiple mounting styles for the front attachment.



JP4 Series inline linear actuator is most similar to the JP3, but was designed for industrial applications that require higher load and speed. Its IP69K protection ensures it will withstand high temp. high pressure water jets, and the ingress of dust and other solid contaminants. For synchronization and position feedback, the JP4 can be equipped with Hall sensors.

Lifting Columns



The TL3 lifting columns from TIMOTION are made up of three extruded aluminum tubes of rectangular shape that give the system great stability and a high stroke with reduced retracted length. This electric lifting column allows for easy integration into many height-adjustable workstation applications, such as an exam chair in the healthcare industry.



TIMOTION's TL4S series lifting columns are specifically designed for use in ergonomic desks and work tables. Using multiple TL series lifting columns with compatible TC series control boxes and TH / TDH series controls, work surfaces can be controlled quietly and smoothly with synchronous movement.



TIMOTION's TL8 series columns are designed with a 3 stage cylindrical appearance and built-in motors. It was designed primarily for use in medical applications. The TL8 provides stable vertical lifting. This makes the engineering design process easier and safer by replacing older style lifting mechanisms that use many moving stages and have pinch points. The TL8 is suitable for the medical bed applications.



TL6 Series. has a three stage telescopic outer tube that is designed for a narrow-top, wide-bottom round appearance, with an inline actuator (TA20) embedded. Without a motor housing design, it is suitable for ergonomic furniture applications. It is the perfect choice for design-oriented lifting furniture in need of a neat structure and space optimization.

Temperature and Humidity Data Loggers & Food Testing Equipment

Single-use USB PDF Data Logger



RC-17/ RC-17N Disposable Single-Use Temp Recorder Data Logger USB

Multi-Use USB Data Logger



RC-4 PDF Temperature Data Logger Multi-function LCD

Wireless temperature data loggers



Elitech Temperature Data Logger WiFi Wireless Monitor, RCW-800W-TDE

Food Testing Equipment



Digital frying oil tester Range °C/°F 40°C - 200°C / 104°F - 392°F



Johnson Oil Quality Test Strips 2.5% Code:244.1 Available in 6% Code:245.1



RC-19 Single Use Temp. Data Logger Temp. Range -30°C to 70°C



Tlog 10 series data loggers internal external temp./ humidity sensor



Elitech Temperature Humidity Data Logger WiFi RCW-800W-THE



Food Contact Safe Probe Disinfectant Wipes Alcohol Free, Quat Free, PHMB Free



Chlorine Tablets for Fruit & Vegetables - 3.2g 1 tablet in 10L cold water=100 ppm



LogEt 1 Single Use PDF Temp. Data Logger (Ext. Sensor) -30°C to 70°C



RC-5+USB Temperature Data Logger automatically generates PD reports



RCW-3000 & RCW-3200 WiFi 4G Wireless Temp. humidity Data Logger



Food Check Hand Held Thermometer



Pro-Surface Thermopen Thermometer for Grills and Hotplates



Tinyusb-10 Waterproof IP67 meets HACCP for food safety



GSP-6G Digital Temp. & Humidity Data Logger Detachable Buffered Probe



RCW-360 Plus WIFI Digital Data Logger Real-Time Temperature



Thermamite HACCP Process Thermometer



Digital COOKING POCKET PEN thermometer -50+300°C/-58+572°F



Elitech LogEt 6 Temperature Data Logger Single Use



RC-51H PDF Temperature Humidity Data Logger



RCW-360 Plus 4G Temp. Humidity Data Logger With External Probe



HI9810352 HALO2 pH Meter for Sushi



Digital Cooking Thermometer 0+300°C/+32+572°F

Water Testing Instrument and Testing Strips

Pool and SPA

Industrial Water / Boiling & Cooling



WaterLink Spin Touch
Code: 3582



SpinDisk Reagent
Code: 4351-H



WaterLink® Spin
Touch® Code: 3581



COD3 Plus Colorimeter
Code: 1925



WaterLink Spin Touch
Code: 3586



Salt/TDS/Cond/Temp
TRACER Code: 1749



pH/SALT/TDS/TEMP
TRACER #1766-KIT-01



pH / Total Chlorine
TRACER #1741-KIT-01



Total Chlorine/pH/ORP
TRACER #1740-KIT-01



Peracetic Acid
0-500ppm #167.5C



Peracetic Acid
0-160ppm #270.1



Peracetic Acid
0-500ppm #168.5C



ColorQ® 2x TesTabs®
PRO 7 Code: 2087



ColorQ® 2x Pool 4 Kit
Code: 2085



ColorQ® 2x PRO 7
Code: 2086



Peracetic Acid
0-2000ppm #228.1



Total Chlorine
0-200ppm #020.5



Chlorine 0-300ppm
Code: 163.1C



Check2O 6 in 1 test
strips Code: 300.001



Check2O 5 in 1 test
strips Code: 301.001



Check2O 4 in 1 test
strips Code: 302.001



J-QUANT® Chlorine
0-1000ppm #164.1C



J-QUANT® Chlorine
0-10,000ppm #268.1



J-QUANT® Peroxide
0-25ppm Code: 220.1



Check2O 3 in 1 test
strips Code: 303.001



Check2O Total Bromine
Code: 306.001



Insta-TEST® Copper
Test Strips #2991-G



J-QUANT® Peroxide
0-100ppm #165.5C



J-QUANT® Peroxide
0-1000ppm #222.1



J-QUANT® Peroxide
0-5000ppm #262.1



Insta-TEST® Iron Test
Strip Code: 2935-G



Low Range Phosphate
Test Strips #3021-G



Sodium Chloride (Salt)
Test Strips Code: 2998



J-QUANT® QAC
25-1000ppm #160.2



QAC 400 Reel
0-400ppm #160.5



J-QUANT® QAC
0-400ppm #160.1

Water Testing Instrument and Testing Strips

Food / Beverage / Laundry & Sanitation

Aquarium Fish Farming

Water Waswater

Soil



Smart3 Colorimeter
Code: 1910



Salt/pH/TDS/Temp
TRACER Code: 1766



Total Chlorine
TRACER Code: 1740



WaterLink® Spin
Touch@FF Code: 3587



DC1500 Chlorine (Free
& Total) Code-3240-LI



Smart 3 Electronic Soil
SCL-12 Code: 1985-05



Chlorine Water Test Kit
Code: 3312-01



The Hygiene™ System
SURE Plus™ rapid ATP



QAC Test Papers
0-400ppm Code:2951



Dissolved Oxygen
TRACER Code:1761



Peroxide Strips
0-50ppm #2984LR



Soil pH Test kit - Color
Chart Code 5024



J-QUANT® Chlorine
0-20ppm Code: 216.1



J-QUANT® Chlorine
0-5ppm Code: 161.1C



Chlorine Test Paper
0-200ppm #145



AQ-4 Salt Water
Aquaculture #3635-05



Peracetic Acid Test
Strip 500ppm #PAA



Garden Guide Soil Test
Kit Code 5679-02



Chlorine Test Paper
0-200ppm #4250-BJ



Peroxide Test Strips
0-90ppm Code: 2984



Peracetic Acid Test
Strips 160ppm #3000



Aquaponics Kit
Code: 3637



Peracetic Acid Test
Strip 3000ppm #PAA



Macronutrient Plant
Tissue Kit #5026-01



Humidity Indicator
Paper Code:016.95



Peroxide Test Strip,
0-400ppm #PER-400



Potato Test Paper
Code: 172-1B-50



Chloride Test Kit
Code: 4503-DR-02



J-QUANT® Iron
0-500ppm #248.1



Model STH-7 - Soil
Testing Outfit #5061



Hardness Low Range
Strips 180ppm #2981



pH indicator strips pH
5.0-9.0 Code: 126.2C



pH indicator strips pH
2.0-9.0 #113.3C



Chlorine Water Test Kit
Code: 3312-01



Peracetic Acid Test
Strip 160ppm #PAA



Plant Nutrition Studies
Code: 5940

Water Testing Instrument and Testing Strips

Drinking Water			Environmental Science	Cosmetics	Homebrew
					
2020t&i Portable Turbidity #1974-t	WaterLink® Spin Touch® DW #3585	pH TRACER PockeTester™ #1741	Ranger Dipslide Incubator #INC-R45	Nutrient TTC-Rose Bengal SKU:M-NUT-RB	Sulfite Test Strip 0-500ppm #SUL1V-50
					
Waterproof Con.TDS-TEMP Portable #AD330	Multi-Parameter pH-ORP-TEMP #AD130	pH-TEMP Pocket Testers Code: AD12	Nutrient TTC SKU: M-NUT-NUT	Tryptic Soy-Rose Bengal #M-TSA-RB-4	Wine pH Test Strips 2.8-4.4 #PH2844
					
Total Coliform / E. COLI #4-3616-UV	Total Coliform BACTERIA #4-3616	Chlorine Bleach Code: 7894-01	Nutrient TTC-Mac Conkey #M-NUT-MAC	pH 7-14 Test Strip, 3 pad #PH0714-3	Beer pH Test Strip 4.6-6.2 #PH4662
					
Free & Total Chlorine 0-10ppm #3027-G	Free Chlorine 0-10ppm #2964-G	Total Chlorine 0-10ppm #2963LR-G	Nutrient TTC-R2A SKU: M-NUT-R2A	pH 2-9 Test Strips, 3 Pad #2090-3-IV-100	Phenolphthalein Paper Code: 029.1
					
Total Chlorine Test Strips 0-5ppm #2979	Low Level Peroxide 0-100ppm #PER-100	Low Level Chlorine 0-10ppm #CHL-10	Protein 0-10ppm #PRO-1V-50	Universal Paper pH 1-11 #0045.1	J-Quant Nitrite Nitrate 500/25 Code: 242.1
					
Biological Activity Reaction Test (BART)	Total Coliform and E.coli Code: 3048	Water Check Now Basic kit Code: 3008	Ammonia 0, 6.0 (ppm) NH3. Code: 3023-G	Universal Paper pH 1-11 Code: 004.1	Water Hardness 0-500ppm #185.1C

Water Testing Instrument and Testing Strips

pH Paper	Qualitative pH Tests	Non-Bleed pH Strips	Reagent Solution	Healthcare	Marine Testing kit
					
Universal Indicator Paper pH 1 - 14 #046.5	Comparator Paper pH 5.4 - 7.0 Code: 053.5	pH 0-14 Universal Indicator Strips #140.4	Buffer Solution pH 4.01 / pH 7.0 / pH 10.0	Extra High Level Peroxide 0-10000ppm	MicrobMonitor@2
					
Universal Indicator Paper pH 1-14 #046.1	Comparator Paper pH 9.0 - 13.0 #058.5	pH indicator strips pH 0 - 2.5 #122.2C	pH Buffer Solution 4.01/6.86/7.9/9.18/10	QAC Test Strips 1500ppm #QAC-1500	Sig Sulphide@ is an SRB test kit
					
Universal Paper pH 1-14 #046.33C	Comparator Paper pH 12.0 - 14.0 #059.5	pH indicator strips pH 2.5 - 4.5 #114.2C	GroLine pH 7.01 Buffer #HI7007-050	Extra High Level QAC 10000ppm	MicrobMonitor@ AQUA™
					
pH 4.5-10 Test Strip, 3 pad #PH4510	Litmus Blue Paper Code: 001.33C	pH indicator strips pH 0 - 6.0 Code: 103.3C	GroLine pH 4.01 Buffer #HI7004-050	Potassium Iodide Starch #160-12V-100	Potable Water Test Kit A. Bacteria & E Coli
					
Universal Indicator Paper pH 1-11 #004.1	Litmus Red Paper Code: 003.33C	pH indicator strips pH 4.0-7.5 Code: 125.2C	DPD Free Chlorine 10mL, 100's #2105569	Chlorine Dioxide 500ppm #CHL-D500	The CMT Sewage Effluent Test Kits
					
Universal Indicator Paper pH 1-11 #004.5	Litmus Neutral Paper Code: 002.33C	pH indicator strips pH 7.0 - 14.0 #109.3C	DPD Total Chlorine 10mL, 100's #2105669	Quick Response QAC Test Strip #QAC-400	Portable Incubator Code: WTK-CT-80020



Mirqab Mall Building, B block second floor
Doha Qatar



+974 3353 4932



+974 3383 6398



sales@caresourceqatar.com
info@caresourceqatar.com



www.caresourceqatar.com

**YOUR ONE STOP SUPPLIER FOR
ALL YOUR LAB NEEDS**